



The **SONOTECH** acoustic underlayment is made out of high density urethane foam and offer superior performances for laminated and wood floors suitable for all floating installations .the high density provide ultimate noise reduction and eliminate moisture with the integrated vapor barrier. The **SONOTECH** also offer good isolation value and will stay resilient in time. The **SONOTECH** is recommended for all types of subfloors including concrete.



### **Specifications**

The **SONOTECH** is a wise choice for all acoustic ,mechanic and thermal properties along with the comfort and stability of wood parquet floor.



COMPOSITION	High density urethane foam with the integrated vapor barrier
COLOR	Tan
WEIGHT	15 pounds
THICKNESS	2 mm (0.078 po)
DENSITY	16 lbs/ pi.cu.
MOISSURE	hydrostatic pression, résistante à l'eau. (AATCC127)
SOUND	70 IIC
FLAMABILITY	meet or exceed federal flammability standard (cpsc-ffl-70)
ANTI-MICROBIAL	Fresh-N-Guard
DIMENSION	3p x 33.3 p (100 pi.ca.)

### **SUPERIOR NOISE REDUCTION (IIC 70,STC 71)**

The Sonotech high density urethane foam features thousands of tiny sound pockets that cushion the floor and deaden noises for better acoustic results.

### **ULTIMATE HUMIDITY CONTROL**

The Sonotech construction is water resistant and has a integrated vapor barrier making it the industry best moisture protection.

### **PREVENT MOLD and MILDEW**

The Sonotech contain anti microbial agent (fresh and gard )protect from the growth of fungus, molds, mildew and harmful bacteria .it is also non allergen and odor free.